

## RH2528

NO.	DESCRIPTION	NO.	DESCRIPTION
1	DUST CAP	53	38 DENS SLANTING GEAR
2	RING SPRING OF DUST CAP 14X1.5	54	CLUTCH SPRING
3	WASHER FOR DUST CAP 16X22X1	55	CLUTCH
4	RING SPRING OF DUST CAP19X2	56	ASWAY-POLED BEARING
5	LOCKING SLEEVE	57	NEEDLE BEARING HK0908
6	WASHER FOR DUST CAP21X32X4	58	ASWAY-POLED BEARING PRESSURE BOARD
7	WASHER C24.8X30.6X1	59	M5X16 CREW
8	STELL BALLC7.14	60	CIRCLIP
9		61	699 BEARING
10	TOWER-SHAPED SCREW	62	MID-AXIAL
11	ST4.1X45SELF-TAPPING BOLT	63	MODEL SELECTOR FORK
12	GEAX BOX	64	MODEL SELECTOR FORK SPRING
13	GEAX BOX COVER	65	609BEARING
14	ST4.2X11SELF-TAPPING BOLT	66	609BEARING PRESSURE BOARD
15	HK0709 NEEDLE BEARING	68	ARMATURE
16	NINE DENS WASHER	69	607BEARING
17	ST4.2X11 SELF-TAPPING BOLT	70	BEARING COVER
18	OIL SEAL 30X41X7	71	BOARD AGAINST WIND
19	HK3012 BEARING SLEEVE	72	ST3.5X16 SELF-TAPPING BOLT
20	HK3012 ROLL PIN	73	STATOR
20	OUTER FLATE RING SPRING OF ROTOR SLEEVE	74	INDUCTANCE D • TOOLS
22	DRILL COVER WASHER	75	SHELL
22	DRILL COVER SPRING	76	SPRING PIECE
23	40 DENS GEAR	70	BRACKET OF ELECTRIC BRUSH
24	DRILL COVER	78	SPRING
25	WASHER	70	ELECTRIC BRUSH
20	CONNECTION DRILL COVER	80	SPRING
28	POSITION-KEY 2.5X12		BACK COVER
20 29	POSITION-LIMITED RING	81 82	ST4.1X16SELF-TAPPING BOLT
	OUTER RING SPRING OF ROTOR SLEEVE		ROTOR INSERT LINE 120MM
30	OIL SEAL 9X16X5	83	SWITCH
31	POSITION-LIMITED SLEEVE OF SPINDLE	84	PRESS CALE BOARD
32	SPINDLE	85	ST3.9X15 SELF-TAPPING BOLT
33	SPINDLE SETS	86	CABLE COVER
34		87	
35	SPINDLE SETS O-RING 16.2X4.5	89	CABLE 2X0.75MM
36	POSITION-LIMITED O-RING 9.6X3.5	90	MODEL SELECTOR KNOB
37	POSITION-LIMITED COVER	91	MODEL SELECTOR O-RING 11X2.5
38	STELL WIRE SPRING 27.5X1.5	92	MODEL SELECTOR SPRING 5.8X44
39	PISTON	93	MODEL SELECTOR IRON CORE
40	PISTONO-RING 15X3	94	MODEL SELECTOR RED KNOB
41	CYLINDER	95	HANDLE STEEL RING
42		96	
43	CYLINDER WASHER	97	HANDLE SEAT
48	BRACKET SLEEVE POWER • C	98	DEPTH GUAGE LOCK SPRING OLS
49	BRACKET O RING	99	DEPTH GUAGE LOCK
50	BRACKET	100	DEPTH GUAGE
51	O-RING 23.8X22	101	M8 BOLT
52	GEAR FIXED	102	ASSISTANT HANDLE